

# SUGITOH · USB CAMERA



TS-CA-200M	
PC Interface ※	USB 2.0 (Posterior and external ports is not available.) ※Partly available.)
Sensor	Color CMOS with 2.0M pixels
Maximum Resolution	SXGA (1280×1024 ) (Real 1600×1200)
Frame Rate	10 fps at SXGA (1280×1024) (Real 1600×1200)
Data Format	RGB 24
Color	Up to 1.68 million True Color (24-bit)
Video Mode ※PC optionally	1280×1024 (Real 1600×1200) / 1024×768
Power Source	From USB 2.0 Cable
Image Control	Color (R/G/B) and Brightness Adjustment, Gamma Correction, Hue, Exposure, Sharpness Adjustment and Gain Control, M·A White Ballanced
Operating System	Windows 2000(Professional·SP4) · XP(Professional·SP2) (Installed to PC at time of shipment from manufacturers only.)
System Requirements ※	CPU equivalent to Intel Pentium III 800MHz processor is minimum requirements. CPU equivalent to Intel Pentium IV 1.5GHz processor or above for the best performance. 256MB RAM. More than 512MB for the best performance. 1 available Hi-Speed USB 2.0 Port (When you use 2-Dimention Measurement & Image Processing Software, in order to use Look Key, need 1 more port.)
C Mount spec · Camera Viewer Software included / Opption : 2-Dimention Measurement / 2-Dimention Measurement & Image Processing Software	

※Please confirm your PC's specification, before use this camera.



SINCE 1906